

Tiger Fall Arrest Blocks (Webbing)

Model No. TIB-W and TIB-WM



Main Features

- Part of the Tigersafe range of height safety equipment
- Lightweight, compact and durable
- Available with 2m, 3.5m and 6m webbing lengths
- Ideal for use in areas where a wire rope could damage fragile items in the work area
- Top anchor point with built-in swivel - limits lifeline twisting (2m, 3.5m and black 6m models)
- Supplied with screw gate karabiner for fitting to a suitable anchor point
- Top scaffold hook available as an option
- Orange 6m model complete with lower self-locking snap hook and swivel with built-in impact indicator
- 2m, 3.5m and 6m black models with "rip stitch indicator" and ultra lightweight self-locking hook
- All fittings meet EN 362:2004
- 140 kg capacity
- Lightweight aluminium housing for 2m and 3.5m models
- Strong, durable, nylon casing for 6m models
- Minimum static strength 15kN
- Easy to inspect
- Super-strong UHMwPE fibre webbing
- 3.5m and 6m models supplied with pull down cord
- Conforms to EN 360:2002
- PPE Regulation (EU)2016/425

New

6m (TIB-06-WM)
nylon casing



6m (TIB-06-W)
nylon casing

2m (TIB-02-W) and
3.5m (TIB-035-W)
aluminium casing

Tiger TIB Fall Arrest Retractable Lifelines/Inertia Reels (PPE Category III) are designed to reduce vertical impact force on the body caused by falling from height. They are used to provide semi-permanent fall protection. The lifeline tension allows the user to move freely around the work area.

Certification:

Each item comes fully certified with a test certificate or an EC Declaration of Conformity. The above items are in conformity with the provisions of Council Directive 89/686/EEC and the standards indicated above.

Technical Data

| Model/Product Code | Length of webbing (m) | Width of webbing (mm) | Net weight (kg) |
|--------------------|-----------------------|-----------------------|-----------------|
| TIB-02-W | 2 | 25 | 1.15 |
| TIB-035-W | 3.5 | 25 | 1.6 |
| TIB-06-W | 6 | 20 | 2.0 |
| TIB-06-WM | 6 | 25 | 2.0 |

- Maximum rated load: 140kg
- Minimum static strength 15kN
- Braking force: less than 6kN
- Operating Temperature: -30°C to +50°C
- PPE Category III Retractable Type Fall Arrestor
- EC Notified Body – SGS

The super-strong ultra-high molecular weight polyethylene (UHMwPE) fibre we use has been verified and certified to OEKO-TEX® Standard 100 based on test report SH004 168403.1



TIB-02-W




TIB-035-W



TIB-06-WM



TIB-06-W



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.