

Home of the Tiger hoisting, clamping, winching and height safety ranges


Tiger Recovery Blocks





Main Features

- Part of the Tigersafe range of height safety equipment
- Lightweight, compact and durable
- Triple pawl brake system with energy dissipating mechanism
- Side cable exit for smooth operation and reduced cable wear
- Ergonomic carrying handle makes transport, set-up and storage easy and safe
- 150kg capacity for operator and tools
- Top anchor point with built-in swivel limits lifeline twisting
- Supplied with screw gate karabiner for fitting to a suitable anchor point
- Top scaffold hook available as an option
- Lower self-locking snap hook and swivel with built-in impact indicator for connecting directly to the safety harness
- All fittings meet EN 362:2004
- Available with 15m or 30m wire rope lengths
- Complete with energy absorber
- Buffer spring at cable exit protects block and allows for smooth operation
- Easy to inspect
- Fully serviceable by an approved Service Agent/Centre
- High strength ABS (thermoplastic) casing
- Side case with metal bush for shaft housing
- Minimum static strength 12kN
- 4.8mm galvanised wire rope
- Supplied with pull down cord
- Conforms to EN 360:2002 and BS EN 1496:2017 Class B
- PPE Regulation (EU)2016/425
- SATRA Certified



Certification:

Each item comes fully certified with a test certificate or an EC Declaration of Conformity. The above items are in conformity with the provisions of Council Directive 89/686/EEC and the standards indicated above.





Home of the Tiger hoisting, clamping, winching and height safety ranges

Technical Data

Model/Product Code	Length of wire (m)	Net weight (kg)	
TRE-15	15	11.8	
TRE-30	30	18.6	

- Maximum rated load: 150kg
- Minimum static strength 12kN
- Braking force: less than 6kN
- Wire Rope 4.8mm galvanised
- Operating Temperature: -30°C to +50°C
- PPE Category III Retractable Type Fall Arrestor





Triple pawl brake system

Technical Data

Product	Dimensions			
Code	Α	В	С	D
TRE 15	293	397	975	176
TRE 30	340	477	1015	200





Double boxed packaging

Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.