

Home of the Tiger pneumatic hoisting, manual hoisting, clamping and winching ranges



Light Snatch Block with Shackle Model No. 8-501

Main Features

- Manufactured with the highest quality tensile steel
- Available from 2 tonnes to 8 tonnes, for wire rope sizes 8mm to 19mm
- Part number, wire rope size and working load limit are marked on each block
- Permanent batch codes link to test certificates for easy traceability
- Supplied with bronze bushings and 4.5"-14" with pressure lube fittings
- Meets or exceeds all requirements of ASME B30.26
- Safety factor 4:1
- Fatigue rated



Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.

Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.



Figure 2

Technical Data

Product Code	Sheave Dia (inch)	Bearing Type	Wire Rope Size (mm)	Capacity (tonnes)*	Net Weight		Replacement Sheave
					Ibs	kg	Replacement Sheave
8-501-02	3.0	BB	8-10	2.0	4	2	8-500-02
8-501-04	4.5	BB	10-13	4.0	13	6	8-500-04
8-501-08	6.0	BB	16-19	8.0	29	13	8-500-08
8-501-0808	8.0	BB	16-19	8.0	44	20	8-500-0808

*Minimum Ultimate Load is 4 times the Working Load Limit 8-501-02/-04 see Figure 1 8-501-08/-0814 see Figure 2

Other sizes available - please ask for details.

Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.