

Home of the Tiger pneumatic hoisting, manual hoisting, clamping and winching ranges



## G80 Eye Self Locking Hook Model No. 8-025

## **Main Features**

Design factor 4:1 proof tested and certified

## **Certification:**

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.


Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.



YOKE G80 FITTINGS

Technical Data									
Product	Capacity	For Grade 80 Chain	Dimensions (mm)						Net Weight
Code	(tonne)	For Grade 80 Chain	Α	D	н	K	Р	Т	(kg)
8-025-07	2.0	7, 8	25	11	24	136	34	20	0.8
8-025-10	3.15	10	33	13	30	167	44	26	1.4
8-025-13	5.3	13	40	16	39	207	51	30	3.0
8-025-16	8.0	16	50	21	49	252	61	36	5.8
8-025-20	12.5	18, 20	62	23	62	281	91	48	8.5
8-025-22	15.0	22	70	24	63	319	80	49	12.5
8-025-26	21.2	26	80	25	69	343	99	56	14.0

Other sizes available - please ask for details.



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.

## Our innovation, your safety