



G80 Swivel Self Locking Hook Model No. 8-027N

Main Features

- Ball bearing performs to fully swivel under load
- Design factor 4:1 proof tested and certified

Certification:


Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.

Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.



Technical Data

Product Code	Capacity (tonne)	For Grade 80 Chain	Dimensions (mm)							Net Weight (kg)
			A	B	D	H	K	P	T	
8-027N-06	1.12	6	32	23	12	19	149	28	15	0.7
8-027N-07	2.0	7, 8	36	29	14	24	186	34	20	1.2
8-027N-10	3.15	10	41	34	16	30	218	44	26	2.0
8-027N-13	5.3	13	46	44	22	39	276	51	30	4.2
8-027N-16	8.0	16	61	51	24	49	329	61	36	7.3
8-027N-20	12.5	18, 20	74	82	26	62	403	91	48	11.7
8-027N-22	15.0	22	97	96	33	63	457	80	49	18.0
8-027N-26	21.2	26	123	116	26	69	535	99	56	32.0



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.