

Home of the Tiger pneumatic hoisting, manual hoisting, clamping and winching ranges



G80 Clevis Grab HookModel No. 8-042

Main Features

- Not for use with Omega Link item 8-018
- No reduction of working load limit, thanks to supporting wings which prevent chain link deformation
- Design factor 4:1 proof tested and certified

Certification:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.




Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.

Technical Data

Product	Capacity	For Grade	Dimensions (mm)						NI_+ \\/_: _+ / \
Code	(tonne)	80 Chain	Α	F	Н	K	L	Р	Net Weight (kg)
8-042-07	2.0	7, 8	9	30	21	54	93	10	0.3
8-042-10	3.15	10	12	41	29	77	128	13	0.8
8-042-13	5.3	13	15	52	37	99	165	16	1.6
8-042-16	8.0	16	18	57	45	114	195	20	2.8
8-042-20	12.5	18, 20	21	73	52	130	222	23	4.8

Other sizes available - please ask for details.



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.