

Home of the Tiger hoisting, clamping, winching and height safety ranges



## **G80 Clevis Sling Latch Hook** Model No. 8-043/S

## **Main Features**

• Design factor 4:1 proof tested and certified

## **Certification:**

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.


Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.



YOKE G80 FITTINGS

Technical Data								
Product Code	Capacity (tonne)	For Grade 80 Chain	Dimensions (mm)					Not Mainht (km)
			Α	Н	K	P1	т	Net Weight (kg)
8-043/S-07	2.0	7, 8	9	22	98	27	18	0.6
8-043/S-10	3.15	10	11	29	121	34	23	1.2
8-043/S-13	5.3	13	14	37	147	44	30	2.3
8-043/S-16	8.0	16	18	42	166	48	39	3.7
8-043/S-20	12.5	18, 20	21	50	200	56	47	6.5

Other sizes available - please ask for details.



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.

## Our innovation, your safety