

G80 Eye Sling Hook with Latch Model No. 8-044/S



Main Features

- Design factor 4:1 proof tested and certified

Certification:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.


Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.



Technical Data

Product Code	Capacity (tonne)	For Grade 80 Chain	Dimensions (mm)						Net Weight (kg)
			A	D	H	K	P1	T	
8-044/S-07	2.0	7, 8	25	12	22	98	28	20	0.5
8-044/S-10	3.15	10	32	15	30	121	36	23	1.0
8-044/S-13	5.3	13	40	18	38	152	40	28	1.7
8-044/S-16	8.0	16	50	22	45	185	44	32	3.2
8-044/S-20	12.5	18, 20	62	27	49	225	45	46	5.5
8-044/S-22	15.0	22	51	31	62	244	73	52	9.0
8-044/S-26	21.2	26	64	35	77	285	77	61	13.5
8-044/S-32	31.5	32	89	40	80	352	114	65	20.0

Other sizes available - please ask for details.



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.