

## Home of the Tiger pneumatic hoisting, manual hoisting, clamping and winching ranges



## G80 Eye Swivel Hook with Ball Bearing Model No. 8-049N

## **Main Features**

- Design factor 4:1 proof tested and certified
- Ball bearing performs full swivel under load

## **Certification:**

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.


Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.



YOKE G80 FITTINGS

l echnical Data										
Product Code	Capacity (tonne)	For Grade 80 Chain	Dimensions (mm)							Not Maight (kg)
			Α	В	D	Н	K	Р	Т	Net Weight (kg)
8-049N-07	2.0	7, 8	36	27	12	22	155	26	18	0.9
8-049N-10	3.15	10	41	37	16	29	189	36	23	1.6
8-049N-13	5.3	13	46	40	21	35	233	42	28	3.4
8-049N-16	8.0	16	61	50	22	44	280	50	35	5.1
8-049N-20	12.5	18, 20	74	82	25	65	356	56	49	9.5

Other sizes available - please ask for details.



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.