

Home of the Tiger hoisting, clamping, winching and height safety ranges



G80 Closed Coupling Master LinkModel No. 8-052

Main Features

• Design factor 4:1 proof tested and certified

Certification:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.


Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.



Technical Data

Duadinat Cada	Commoity (tonno)	Fau Cunda 00 Chain		Dime	ensions (n	nm)		NI -+ \N/ -! -+ / \			
Product Code	Capacity (tonne)	For Grade 80 Chain	Н	K	L	Т	W	Net Weight (kg)			
8-052-10	3.15	10	19	127	101	19	65	0.7			
8-052-16	8.0	16	26	174	137	25	80	1.7			
8-052-20	12.5	18, 20	36	202	165	31	104	3.0			

Other sizes available - please ask for details.



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.