

Home of the Tiger pneumatic hoisting, manual hoisting, clamping and winching ranges

G80 Half Coupling Link with Coupling Pin and Sleeve LockingModel No. 8-054




Main Features

Design factor 4:1 proof tested and certified

Certification:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.






Technical Data

| Consider (towns) | For Grade 80 Chain | Dimensions (mm) | | | | Not Mainbt (kg) |
|------------------|----------------------------|--|---|---|--|---|
| Capacity (tonne) | | Α | D | K | L | Net Weight (kg) |
| 2.0 | 7, 8 | 18 | 9 | 22 | 28 | 0.1 |
| 3.15 | 10 | 25 | 11 | 26 | 34 | 0.2 |
| 5.3 | 13 | 30 | 16 | 35 | 45 | 0.4 |
| 8.0 | 16 | 36 | 19 | 38 | 50 | 0.6 |
| 12.5 | 18, 20 | 42 | 22 | 46 | 60 | 1.1 |
| 15.0 | 22 | 49 | 24 | 59 | 76 | 1.7 |
| | 3.15 5.3 8.0 12.5 | 2.0 7, 8 3.15 10 5.3 13 8.0 16 12.5 18, 20 | 2.0 7, 8 18 3.15 10 25 5.3 13 30 8.0 16 36 12.5 18, 20 42 | Capacity (tonne) For Grade 80 Chain A D 2.0 7, 8 18 9 3.15 10 25 11 5.3 13 30 16 8.0 16 36 19 12.5 18, 20 42 22 | Capacity (tonne) For Grade 80 Chain A D K 2.0 7, 8 18 9 22 3.15 10 25 11 26 5.3 13 30 16 35 8.0 16 36 19 38 12.5 18, 20 42 22 46 | Capacity (tonne) For Grade 80 Chain A D K L 2.0 7, 8 18 9 22 28 3.15 10 25 11 26 34 5.3 13 30 16 35 45 8.0 16 36 19 38 50 12.5 18, 20 42 22 46 60 |

Other sizes available - please ask for details.



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.