

Oilfield Hoist Block Model No. 8-591



Main Features

- Manufactured with the highest quality alloy steel
- Available from 4 tonnes to 30 tonnes, for wire rope sizes 8mm to 20mm
- Part number, wire rope size and working load limit are marked on each block
- Permanent batch codes link to test certificates for easy traceability
- Supplied with sealed tapered bearings for extended product life and faster line speeds
- Safety factor 4:1
- Manufactured by an API Q1 certified facility



Certification:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.

Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.

Technical Data

Product Code	Sheave Dia (inch)	Bearing Type	Wire Rope Size (mm)	Capacity (tonnes)*	Net Weight	
					Ibs	kg
8-591-0408	8	TB	10-13	4.0	35	16.0
8-591-0810-13	10	TB	10-13	8.0	55	25.0
8-591-0810-15	10	TB	13-15	8.0	55	25.0
8-591-1214-19	14	TB	19	12.0	95	43.0

*Minimum Ultimate Load is 4 times the Working Load Limit
TB = Tapered Bearing

Other sizes available - please ask for details.

Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.