





Main Features

- Shackles are Type Approved by DNV & ABS
- Forged carbon steel with alloy pin •

v.tigerliftinc

- Size and the working load limit permanently shown on each shackle •
- All shackles have a batch code which links to test certificate and quality traceability
- 100% magnaflux crack detection during manufacturing •
- 20,000 cycle fatigue rated to 1.5 times working load limit

Home of the Tiger pneumatic hoisting, manual hoisting, clamping and winching ranges

Galvanized finish


Certification:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.

Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.

| Technical Data | | | | | | | | | | | |
|----------------|--------------|---------------------|----------------------|-----------------|----|----|----|----|-----|----|-----------------|
| | Product Code | Capacity (tonne) | Nominal Size (mm) | Dimensions (mm) | | | | | | | |
| | | | | Α | В | D | E | G | н | W | Net Weight (kg) |
| | 8-837-13 | 2.00 | 13 | 47 | 13 | 16 | 33 | 30 | 85 | 20 | 0.3 |
| | 8-837-16 | 3.25 | 16 | 61 | 16 | 19 | 43 | 38 | 106 | 27 | 0.6 |
| | 8-837-19 | 4.75 | 19 | 72 | 19 | 22 | 50 | 46 | 126 | 33 | 1.0 |
| | 8-837-26 | 8.50 | 26 | 96 | 26 | 28 | 69 | 61 | 166 | 44 | 2.3 |

Other sizes available - please ask for details.



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.



